

Novagloss® 195 RT

Sheetfed Offset

Black Inks

Characteristics	<p>Novagloss® 195 RT Black is an enhanced oxidatively drying all-round black series offering a very high gloss level.</p> <p>It is excellently suited for machines of the latest generation, but also for printing machines of older generations.</p>				
Drying properties	Oxidative drying				
Substrates	Excellently suited for coated papers, conditionally suited for uncoated papers and board.				
Remarks and special information	<p>Novagloss® 195 RT Black dries fast and features an excellent rub resistance. It is therefore well suited where the mechanical stress is high.</p> <p>Suited for printing work corresponding to ISO 12647-2.</p>				
Fastness properties	Light	Alcohol	Solvent mixture	Alkali	Hot calendering
<i>Novagloss® 195 RT, blue-toned</i>	8	-	-	+	-
	<p>Light fastness: according to ISO 12040 from 1 (low) to 8 (high)</p> <p>Fastness: according to ISO 2836</p> <p>+ = Resistance provided</p> <p>- = Resistance not provided</p>				

Version: 05.08.2009



The aim of our technical documents is to inform and advise our customers. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that these advice documents cannot be used as the basis for claims in law.

Product names followed by ® are trademarks registered by Flint Group Incorporated.

Flint Group Germany GmbH
 Sieglestrasse 25
 70469 Stuttgart, Germany
 T +49 711 98 16-0
 F +49 711 98 16-700
 E info@eu.flintgrp.com
 I www.flintgrp.com