

## Offset Black 110

## Sheetfed Offset

## Black Inks

<b>Characteristics</b>	<b>Offset Black 110</b> is a non-oxidative drying all-round black. It is excellently suited for printing machines for indirect letterpress printing and book printing.				
<b>Drying properties</b>	Non oxidative drying				
<b>Substrates</b>	Ideal suited for glossy coated paper and carton. Good results on coated paper and carton.				
<b>Remarks and special information</b>	Due to the non oxidative drying formulation of <b>Offset Black 110</b> a longer drying time has to be taken into consideration compared to the regular application of standard sheetfed inks. Suited for printing work corresponding to ISO 12647-2.				
<b>Fastness properties</b>	<b>Light</b>	<b>Alcohol</b>	<b>Solvent mixture</b>	<b>Alkali</b>	<b>Hot calendering</b>
<i>Offset Black 110, blue-toned</i>	8	-	-	+	-
	<b>Light fastness:</b> according to ISO 12040 from 1 (low) to 8 (high) <b>Fastness:</b> according to ISO 2836 + = Resistance provided - = Resistance not provided				

Version: 05.08.2009



The aim of our technical documents is to inform and advise our customers. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that these advice documents cannot be used as the basis for claims in law.

**Flint Group Germany GmbH**  
 Sieglestrasse 25  
 70469 Stuttgart, Germany  
 T +49 711 98 16-0  
 F +49 711 98 16-700  
 E info@eu.flintgrp.com  
 I www.flintgrp.com